

二]性能表

型号	叶轮型式	流量 m ³ /h	扬程 m	效率 %	功率 Kw		必需汽蚀 余量 m	转速 r/min
					轴功率	电机功率		
40-100	0	5.04	15.2	46	0.39	0.75	2.0	2900
		6.30	12	50	0.41		2.0	
		7.56	10	53	0.43		2.5	
	A	4.50	12.8	45	0.30	0.75	2.0	
		5.60	10	48	0.32		2.0	
		6.66	8	49	0.35		2.5	
40-100J	0	2.52	3.8	42	0.06	0.55	2.0	1450
		3.2	3	48	0.06		2.0	
		3.8	2.5	51	0.05		2.5	
	A	2.25	3.2	40	0.05	0.55	2.0	
		2.8	2.5	46	0.04		2.0	
		3.33	2	49	0.04		2.5	
40-125	0	5.04	23.5	43	0.74	1.5	2.0	2900
		6.30	20	46	0.75		2.0	
		7.56	18	50	0.75		2.5	
	A	4.50	19.5	42	0.54	1.1	2.0	
		5.60	16	44	0.56		2.0	
		6.66	14.4	48	0.57		2.5	
40-125J	0	2.52	5.88	41	0.10	0.55	2.0	1450
		3.2	5	44	0.10		2.0	
		3.8	4.5	48	0.10		2.5	
	A	2.25	4.9	39	0.08	0.55	2.0	
		2.8	4	42	0.07		2.0	
		3.33	3.6	46	0.07		2.5	
40-160	0	5.04	34.5	41	1.16	2.2	2.0	2900
		6.30	32	45	1.22		2.0	
		7.56	30	49	1.26		2.5	
	A	4.50	30.5	40	0.92	1.5	2.0	
		5.60	28	43	0.99		2.0	
		6.66	26.3	47	1.02		2.5	
40-160J	0	2.52	8.6	39	0.15	0.75	2.0	1450
		3.2	8	43	0.16		2.0	
		3.8	7.5	47	0.17		2.5	
	A	2.25	7.5	37	0.12	0.75	2.0	
		2.8	7	41	0.13		2.0	
		3.33	6.6	45	0.13		2.5	
40-200	0	5.04	55	35	2.05	4	2.0	2900
		6.30	52.5	38	2.26		2.0	
		7.56	48	41	2.41		2.5	

	A	4.50 5.60 6.66	49 46.5 42	34 36 39	1.77 1.97 1.95	3	2.0 2.0 2.5
40-200J	O	2.52	13.8	34	0.28	1.1	2.0
		3.2	13.1	37	0.31		2.0
		3.8	12	39	0.32		2.5
	A	2.25	12.2	33	0.23	1.1	2.0
		2.8	11.6	35	0.25		2.0
		3.33	10.5	37	0.26		2.5
50-125	O	7.5	22.0	47	0.96	2.2	2.0
		12.5	20.0	60	1.13		2.0
		15.0	18.5	60	1.26		2.5
	A	7.2	20.0	46	0.85	2.2	2.0
		11.9	18.2	58	1.02		2.0
		14.3	16.8	58	1.13		2.25
	B	6.7	17.5	45	0.71	1.5	2.0
		11.2	15.9	56	0.86		2.0
		13.4	14.7	56	0.96		2.05
	C	6.2	15.2	44	0.59	1.1	2.0
		10.4	13.8	54	0.72		2.0
		12.5	12.8	54	0.80		2.0
50-125J	O	3.8	5.4	43	0.13	0.55	2.0
		6.3	5.0	54	0.16		2.0
		7.5	4.6	55	0.17		2.5
	A	3.6	4.9	42	0.11	0.55	2.0
		6.0	4.6	52	0.14		2.0
		7.2	4.2	53	0.15		2.25
	B	3.4	4.3	41	0.10	0.55	2.0
		5.6	4.0	50	0.12		2.0
		6.7	3.7	51	0.13		2.05
	C	3.1	3.7	40	0.08	0.55	2.0
		5.2	3.5	48	0.10		2.0
		6.2	3.2	49	0.11		2.0
50-160	O	7.5	34.2	44	1.59	3	2.0
		12.5	32	54	2.02		2.0
		15.0	29.6	56	2.16		2.5
	A	6.8	28.4	41.5	1.27	3	2.0
		11.4	26.6	52	1.59		2.0
		13.7	24.6	53	1.73		2.16
	B	6.1	22.5	39	0.95	2.2	2.0
		10.1	21.0	50	1.16		2.0
		12.2	19.4	51	1.26		2.0

	C	5.4 9.0 10.8	17.9 16.7 15.4	36 45 45.5	0.73 0.91 1.0	1.5	2.0 2.0 2.5	
50-160J	O	3.8	8.5	35	0.25	0.55	2.0	1450
		6.3	8.0	48	0.29		2.0	
		7.5	7.5	49	0.31		2.5	
	A	3.4	7.1	34	0.19	0.55	2.0	
		5.7	6.7	45.5	0.23		2.0	
		6.8	6.2	46	0.25		2.16	
	B	3.0	5.6	32	0.14	0.55	2.0	
		5.1	5.3	42	0.17		2.0	
		6.1	4.9	42.5	0.19		2.0	
	C	2.7	4.4	30	0.11	0.55	2.0	
		4.6	4.2	38	0.14		2.0	
		5.4	3.9	38.5	0.19		2.0	
50-200	O	7.5	52.5	38	2.82	5.5	2.0	2900
		12.5	50.0	48	3.54		2.0	
		15.0	48.0	51	3.95		2.5	
	A	7.3	49.0	37.5	2.61	5.5	2.0	
		12.1	47.0	47	3.60		2.0	
		14.6	45.0	50	3.58		2.3	
	B	7.0	45.3	37	2.33	4	2.0	
		11.47	43.2	46.2	2.96		2.0	
		14.0	41.5	49.2	3.20		2.15	
	C	6.5	39.6	36	1.95	4	2.0	
		10.9	37.7	45.2	2.47		2.0	
		13.0	36.2	48.2	2.67		2.0	
50-200J	O	3.8	13.1	33	0.41	0.75	2.0	1450
		6.3	12.5	42	0.51		2.0	
		7.5	12	44	0.56		2.15	
	A	3.6	12.3	32.5	0.38	0.75	2.0	
		6.1	11.8	41.5	0.47		2.0	
		7.3	11.3	43.2	0.52		2.3	
	B	3.5	11.3	32	0.34	0.75	2.0	
		5.9	10.8	40.7	0.42		2.0	
		7.0	10.4	42.5	0.46		2.5	
	C	3.3	9.9	31	0.28	0.55	2.0	
		5.5	9.4	39.5	0.36		2.0	
		6.5	9.1	41.2	0.39		2.0	
50-250	O	7.5	82.0	28.5	5.87	11	2.0	2900
		12.5	80.0	38	7.16		2.0	
		15.0	78.5	41	7.83		2.5	

	A	7.0	70.6	28	4.78	11	2.0	1450
		11.6	68.9	37.5	5.80		2.0	
		13.9	67.6	40	6.41		2.3	
	B	6.5	61.2	27.5	3.93	7.5	2.0	
		10.8	59.7	36.3	4.84		2.0	
		13.0	58.6	39	5.30		2.0	
	C	6.0	52.5	27	3.18	5.5	2.0	
		10.0	51.2	35	3.98		2.0	
		12.0	50.2	37.5	4.38		2.0	
50-250J	O	3.8	20.5	23	0.91	1.5	2.0	1450
		6.3	20	32	1.07		2.0	
		7.5	19.5	35	1.14		2.5	
	A	3.5	17.7	22.1	0.76	1.5	2.0	
		5.9	17.2	31.2	0.88		2.0	
		7.0	16.8	34.2	0.93		2.25	
	B	3.2	15.3	21.5	0.63	1.5	2.0	
		5.4	14.9	30.5	0.73		2.0	
		6.5	14.6	33.5	0.77		2.05	
C	3.0	13.1	21	0.51	1.1	2.0		
	5.0	12.8	29.5	0.60		2.0		
	6.0	12.5	32.5	0.63		2.0		
65-125	O	15.0	21.8	58.0	1.54	3	2.0	2900
		25.0	20.0	69.0	1.97		2.5	
		30.0	18.5	68.0	2.22		3.0	
	A	14.1	19.2	55	1.33	3	2.0	
		23.5	17.6	67	1.68		2.3	
		28.2	16.3	66	1.89		2.6	
	B	13.2	16.8	50.5	1.19	2.2	2.0	
		21.9	15.4	62	1.48		2.3	
		26.3	14.2	61	1.67		2.6	
C	11.3	12.4	43.5	0.88	2.2	2.0		
	18.9	11.4	53	1.10		2.15		
	22.6	10.5	52	1.25		2.4		
65-125J	O	7.5	5.4	53	0.21	0.55	2.0	1450
		12.5	5.0	64	0.27		2.0	
		15	4.7	65	0.31		2.5	
	A	7.0	4.7	50.5	0.18	0.55	2.0	
		11.7	4.4	61.5	0.23		2.0	
		14.1	4.1	62	0.26		2.3	
	B	6.6	4.1	46.5	0.16	0.55	2.0	
		11.0	3.8	57	0.20		2.0	
		13.2	3.6	57.5	0.23		2.15	

	C	5.7 9.4 11.3	3.0 2.8 2.7	51.5 48 48.5	0.11 0.15 0.17	0.55	2.0 2.0 2.0	
65-160	O	15.0	35.0	54	2.65	5.5	2.0	2900
		25.0	32.0	65	3.35		2.0	
		30.0	30.0	66	3.71		2.5	
	A	14.1	30.8	52.5	2.25	4	2.0	
		23.5	28.2	63	2.86		2.0	
B	28.2	26.4	64	3.16	4	2.25		
	13.0	26.1	49.5	1.86		2.0		
	21.6	23.9	58	2.42		2.0		
C	25.9	22.4	49	2.68	3	2.05		
	12.0	22.5	46.8	1.5		2.0		
	20.1	20.6	55	2.05		2.0		
65-160J	O	7.5	8.8	50	0.36	0.75	2.0	1450
		12.5	8.0	50	0.45		2.0	
		15	7.2	60	0.49		2.5	
	A	7.0	7.8	47	0.32	0.75	2.0	
		11.7	7.0	58	0.39		2.0	
		14.4	6.3	58	0.42		2.25	
	B	6.5	5.6	45.5	0.25	0.55	2.0	
		10.8	6.0	55	0.32		2.0	
		13	5.4	55	0.35		2.05	
	C	6.0	5.7	43	0.22	0.55	2.0	
		10.0	5.2	52	0.27		2.0	
		12.0	4.6	52	0.29		2.0	
65-200	O	15.0	53.0	49	4.42	7.5	2.0	2900
		25.0	50.0	60	5.67		2.0	
		30.0	47.0	61	6.29		2.5	
	A	14.3	47.8	48.7	3.81	7.5	2.0	
		23.8	45.1	59.5	4.91		2.0	
		28.5	42.4	60.5	5.44		2.3	
型号	叶轮型式	流量 m ³ /h	扬程 m	效率 %	功率 Kw		必需汽蚀 余量 m	转速 r/min
					轴功率	电机功率		
65-200	B	13.5	42.9	48.3	3.27	5.5	2.0	2900
		22.5	40.5	59	4.21		2.0	
		27.0	38.1	60	4.67		2.1	
	C	12.8	38.3	48	2.77	5.5	2.0	
		21.3	36.1	57.5	3.64		2.0	
		25.5	34.0	59	4.00		2.0	
65-200J	O	7.5	13.2	43	0.63	1.1	2.0	1450

		12.5 15	12.5 11.8	55 57	0.77 0.85		2.0 2.5	
	A	7.1 11.9 14.3	11.9 11.3 10.7	43 55 57	0.54 0.66 0.73	1.1	2.0 2.0 2.3	
	B	6.8 11.3 13.5	10.7 10.1 9.6	43 55 57	0.46 0.56 0.62	1.1	2.0 2.0 2.1	
	C	6.4 10.6 12.8	9.5 9.0 8.5	43 55 57	0.39 0.48 0.52	0.75	2.0 2.0 2.0	
65-250	O	15.0 25.0 30.0	82 80.0 78	37 50 53	9.05 10.9 12.0	15	2.0 2.0 2.5	2900
	A	14.1 23.4 28.1	72.0 70.2 68.5	36.5 49 52.4	7.55 9.14 10.0	15	2.0 2.0 2.3	
	B	13.1 21.9 26.2	62.7 61.1 59.6	36 47.6 51	6.22 7.64 8.34	11	2.0 2.0 2.0	
	C	12.3 20.5 24.6	55.0 53.7 52.3	35.5 46.3 49.7	5.18 6.46 7.04	11	2.0 2.0 2.0	
65-250J	O	7.5 12.5 15	21 20 19.4	35 46 48	1.23 1.48 1.65	2.2	2.0 2.0 2.5	1450
	A	7.0 11.7 14.1	18.4 17.6 17.0	35 44.8 47	1.01 1.25 1.39	2.2	2.0 2.0 2.26	
	B	6.6 10.9 13.1	16.0 15.3 14.8	34.8 43.8 46.2	0.82 1.04 1.15	1.5	2.0 2.0 2.07	
	C	6.1 10.2 12.3	14.1 13.4 13.0	34.5 43 45	0.68 0.87 0.97	1.5	2.0 2.0 2.0	
65-315	O	15 25 30	127 125 123	28 40 44	18.5 21.3 22.8	30	2.5 2.5 3.0	2900
	A	14 23.3 28.0	111 109 107	28 39.5 43.5	15 17.5 18.5	22	2.5 2.5 2.75	
	B	13.1	97.5	28	12.5	18.5	2.5	

		21.9 26.3	96.0 94.4	39 43	14.7 15.7		2.5 2.56			
	C	12.1 20.2 24.3	83.2 81.9 80.6	28 38.5 42.5	9.83 11.7 12.5	15	2.5 2.5 2.5			
65-315J	O	7.5 12.5 15	32.3 32 31.7	25 37 41	2.63 2.94 3.16	4	2.5 2.5 3.0	1450		
		A	7.0 11.7 14.0	28.1 27.9 27.6	25 36.6 40.6	2.15 2.42 2.58	4		2.5 2.5 2.75	
			B	6.6 11.0 13.1	24.8 24.6 24.3	25 36.3 40.6	1.78 2.02 2.15		3	2.5 2.5 2.56
	C	6.1 10.1 12.1		21.2 21.0 20.8	25 36 40.4	1.41 1.61 1.70	3		2.5 2.5 2.5	
		O		30 50 60	22.5 20 18	54 75 74	2.87 3.63 3.93		5.5	3.0 3.0 3.5
			A	28.7 47.9 57.4	20.6 18.3 16.5	63 73 72.5	2.56 3.27 3.56		5.5	3.0 3.0 3.3
B	26.1 43.6 52.3			17.1 15.2 13.7	60.5 69.5 68.5	2.01 2.59 2.84	4	3.0 3.0 3.1		
	C	23.1 38.6 46.3		13.4 11.9 10.7	58 65.5 64.5	1.45 1.91 2.09	3	3.0 3.0 3.0		
80-125J		O	15 25 30	5.6 5.2 4.5	55 71 72	0.42 0.78 0.51	0.75	2.5 2.5 3.0	1450	
	A		14.4 23.9 28.7	5.1 4.6 4.1	54.5 70 71	0.37 0.43 0.45	0.75	2.5 2.5 2.8		
			B	13.1 21.8 26.1	4.3 3.8 3.4	53 66 67	0.29 0.34 0.36	0.55		2.5 2.5 2.55
		C		11.6 19.3 23.1	3.3 3.0 2.7	51 62 63	0.21 0.25 0.27	0.55		2.5 2.5 2.5
	80-160		O	30	36	61	4.82	7.8		2.5

80-160J	A	50	32	73	5.97	7.5	2.5	2900	
		60	29	72	6.59		3.0		
		28.2	31.7	60	4.05		2.5		
	B	46.9	28.2	71	5.07	5.5	2.5		
		56.3	25.5	70	5.59		2.8		
		25.9	26.9	59	3.21		2.5		
	C	43.2	23.9	67	4.2	5.5	2.5		
		51.9	21.7	66	4.63		2.6		
		24.1	23.2	57	2.67		2.5		
	80-160J	O	40.1	20.6	64	3.52	1.5		2.5
			48.2	18.7	63	3.89			2.5
			15	9	55	0.67			2.5
A		25	8	69	0.79	1.1	2.5		
		30	7.2	68	0.86		3.0		
		14.1	7.9	53.5	0.57		2.5		
		23.5	7.0	66.5	0.68		2.5		
		28.2	6.3	66.5	0.74		2.8		
型号	叶轮型式	流量 m ³ /h	扬程 m	效率%	功率 Kw		必需汽蚀余量 m	转速 r/min	
					轴功率	电机功率			
80-160J	B	13.0	6.7	51	0.47	1.1	2.5	1450	
		21.6	6.0	63	0.56		2.5		
		25.9	5.4	62	0.61		2.6		
	C	12.0	5.8	48	0.4	0.75	2.5		
		20.1	5.2	60	0.47		2.5		
		24.1	4.6	59	0.52		2.5		
80-200	O	30	53	55	7.87	15	2.5	2900	
		50	50	69	9.87		2.5		
		60	47	71	10.8		3.0		
	A	28.0	40.6	54.5	6.42	11	2.5		
		46.9	43.3	67	8.21		2.5		
		55.9	40.8	69.5	8.93		2.7		
	B	25.6	38.6	53.5	5.02	11	2.5		
		42.7	36.4	66	6.40		2.5		
		51.2	34.2	68.5	6.96		2.5		
	C	23.5	32.6	52.5	3.98	7.5	2.5		
		39.2	30.8	64.5	5.09		2.5		
		47.1	28.9	68	5.45		2.5		
80-200J	O	15	13.2	51	1.06	2.2	2.5	1450	
		25	12.5	65	1.31		2.5		
		30	11.8	67	1.44		2.5		
	A	14.0	11.5	50.6	0.83	1.5	2.5		
		23.3	10.9	63	1.09		2.5		

80-250	B	27.9	10.2	65	1.20	1.5	3.0	1450
		12.8	9.6	49.4	0.68		2.5	
		21.3	9.1	61.5	0.86		2.5	
		25.6	8.6	62.5	0.96		2.7	
	C	11.8	8.1	48	0.54	1.1	2.5	
		19.6	7.7	60.5	0.68		2.5	
		23.5	7.3	61.5	0.76		2.53	
		30	84	52	13.2		22	
50	80	63	17.3	2.5				
60	75	64	19.2	2.5				
A	28.3	74.9	52.3	11	22	2.5		
	47.2	71.3	62.5	14.6		2.5		
	56.6	66.8	64	16.1		3.0		
	B	26.6	66.2	52.5		9.1	18.5	2.5
44.4		63.1	62.2	12.3	2.5			
53.3		59.1	64	13.4	2.8			
C		23.8	52.7	53	6.43	15		2.5
	39.6	50.2	60.8	8.9	2.5			
	47.5	47.0	63	9.59	2.5			
	80-250J	O	15	21	49		1.75	3
25			20	60	2.27	2.5		
30			18.8	61	2.52	3.0		
A		14.2	18.7	49	1.47	3	2.5	
		23.6	17.8	58.7	1.95		2.5	
		28.3	16.8	59.7	2.16		2.8	
B		13.3	16.6	49	1.23	2.2	2.5	
		22.2	15.8	58	1.64		2.5	
	26.6	14.8	59.5	1.84	2.6			
C	11.9	13.2	49	0.87	2.2	2.5		
	19.8	12.6	57	1.19		2.5		
	23.8	11.8	59	1.29		2.5		
型号	叶轮型式	流量 m ³ /h	扬程 m	效率%	功率 Kw		必需汽蚀余量 m	转速 r/min
					轴功率	电机功率		
80-315	O	30	128	41	25.5	37	2.5	2900
		50	125	54	31.5		2.5	
		60	123	57	35.5		3.0	
		28.0	112	41	20.7		2.5	
	A	46.7	109	53.5	25.9	37	2.5	
		56.0	107	56.7	28.8		2.7	
		B	26.3	98.3	41		17.2	
	43.8		96.0	53	21.6	2.5		
52.6	94.4		56	24.0	2.6			

	C	24.3 40.5 48.6	83.9 81.9 80.6	41 52.5 53	13.5 17.2 19	22	2.5 2.5 2.5	
80-315J	O	15	32.5	39	3.4	5.5	2.5	1450
		25	32	52	4.19		2.5	
		30	31.5	56	4.6		3.0	
	A	14.0	28.3	39	2.77	5.5	2.5	
		23.3	27.9	51.7	3.43		2.5	
		28.0	27.4	55.8	3.75		2.7	
	B	13.1	25	39	2.29	4	2.5	
		21.9	24.6	51.4	2.85		2.5	
		26.3	24.2	55.6	3.11		2.63	
	C	12.1	21.3	39	1.81	4	2.5	
		20.2	21.0	51.1	2.26		2.5	
		24.3	20.6	55.4	2.46		2.5	
100-125	O	60	24	67	5.86	11	4.0	2900
		100	20	78	7.0		4.5	
		120	16.5	74	7.28		5.0	
	A	56.6	21.3	63.5	5.17	11	4	
		94.2	17.8	73	6.25		4.4	
		113	14.7	70	6.45		4.8	
	B	53.5	19.1	60	4.64	7.5	4.0	
		89.2	15.9	70	5.52		4.2	
		107	13.1	65	5.89		4.4	
	C	47.9	15	54.5	3.57	5.5	4.0	
		79.1	12.5	64	4.22		4.2	
		95.0	10.3	62.5	4.28		4.4	
100-125J	O	30	6	64	0.77	1.5	2.5	1450
		50	5	75	0.91		2.5	
		60	4	71	0.92		3.0	
	A	28.3	5.3	61	0.67	1.5	2.5	
		47.1	4.4	72	0.79		2.5	
		56.6	3.6	66	0.83		2.8	
	B	56.8	4.8	57	0.61	1.1	2.5	
		44.6	4.0	66	0.73		2.5	
		53.5	3.2	64	0.73		2.6	
	C	23.7	3.8	48	0.51	1.1	2.5	
		39.6	3.1	61	0.55		2.5	
		47.5	2.5	59	0.55		2.5	
100-160	O	60	36	70	8.4	15	3.5	2900
		100	32	78	11.1		4.0	
		120	28	75	12.2		5.0	

	A	56.9 94.8 114	32.4 28.8 25.2	69.7 77.5 74.2	7.2 9.6 10.5	15	3.5 3.9 4.5	
型号	叶轮型式	流量 m ³ /h	扬程 m	效率%	功率 Kw		必需汽蚀余量 m	转速 r/min
					轴功率	电机功率		
100-160	B	53.4	28.5	69	6	11	3.5	2900
		89.0	25.4	77	8		3.8	
		107	22.2	74	8.8		4.1	
	C	50.6	25.6	69	5.1	11	3.5	
		84.4	22.8	76	6.9		3.6	
		101	19.9	74	7.5		3.9	
100-160J	O	30	9.2	67	1.12	2.2	2.5	1450
		50	8.0	75	1.45		2.5	
		60	6.8	71	1.57		3.5	
	A	28.4	8.3	67	0.96	2.2	2.5	
		47.4	7.2	76	1.22		2.34	
		56.9	6.1	70	1.35		2.9	
	B	26.7	7.3	66	0.8	1.5	2.0	
		44.5	6.3	73.3	1.05		2.25	
		53.4	5.4	69	1.14		2.6	
	C	25.3	6.6	65.5	0.68	1.5	2.0	
		42.2	5.7	73	0.90		2.17	
		50.6	4.8	68.5	0.97		2.4	
100-200	O	60	54	65	13.6	22	3.0	2900
		100	50	76	17.9		3.6	
		120	47	77	19.9		4.8	
	A	56.4	47.8	65	11.3	22	3.0	
		94.1	44.2	76.5	14.8		3.5	
		113	41.6	77	16.6		4.3	
	B	53.5	42.9	65	9.6	18.5	3.0	
		89.1	39.7	74.5	12.9		3.4	
		107	37.3	76	14.3		3.6	
	C	50.5	38.3	65	8.09	15	3.0	
		84.2	35.4	73	11.1		3.2	
		101	33.3	75	12.2		3.6	
100-200J	O	30	13.5	60	1.84	4	2.0	1450
		50	12.5	73	2.33		3.2	
		60	11.8	74	2.61		2.5	
	A	28.2	11.9	60	1.53	3	2.0	
		47	11.1	72.7	1.95		2.0	
		56.4	10.4	73.7	2.18		2.29	
	B	26.7	10.7	60	1.30	3	2.0	

		44.6 53.5	9.9 9.4	72.3 73.3	1.67 1.86		2.0 2.15	
	C	25.3 42.1 50.5	9.6 8.9 8.4	60 72 73	1.10 1.41 1.57	2.2	2.0 2.0 2.0	
100-250	O	60	87	61	23.4	37	3.5	2900
		100	80	72	30.3		3.8	
		120	74.5	73	33.3		4.8	
	A	56.0	75.8	59.5	19.4	37	3.5	
		93.3	69.7	70	25.6		3.7	
		112	64.9	70.5	28.1		4.4	
	B	52.2	65.9	56.5	16.6	30	3.5	
		87.1	60.6	66	21.8		3.5	
	C	104	56.5	67	24.0	30	4.0	
		48.5	56.8	53	14.1		3.5	
		80.8	52.2	63	18.3		3.5	
			96.6	48.6	67	20.1		
型号	叶轮型式	流量 m ³ /h	扬程 m	效率%	功率 Kw		必需汽蚀余量 m	转速 r/min
					轴功率	电机功率		
100-250J	O	30	21.3	55	3.16	5.5	2.0	1450
		50	20	58	4.00		2.0	
		60	19	70	4.44		2.5	
	A	28.0	18.6	53	2.67	5.5	2.0	
		46.7	17.4	65.5	3.38		2.0	
		56.0	16.6	67.8	3.72		2.25	
	B	26.1	16.1	51	2.25	4	2.0	
		43.5	15.2	62	2.90		2.0	
		52.2	14.4	64.4	3.17		2.05	
	C	24.2	13.9	49	1.87	4	2.0	
		40.4	13.1	58.5	2.45		2.0	
		48.5	12.4	60.6	2.70		2.0	
100-315	O	60	133	55	39.6	75	3.0	2900
		100	125	60	51.6		3.6	
		120	118	67	57.5		4.2	
	A	56	116	55	32.1	55	3.0	
		93.3	109	63	42.5		3.4	
		112	103	66	47.5		3.9	
	B	52.6	102	55	26.6	45	3.0	
		87.6	96	64.5	35.5		3.3	
		105	90.6	65	39.9		3.7	
	C	48.5	87.2	55	21.0	37	3.0	
		81.0	81.9	63	28.7		3.2	

		97.1	77.3	64	32		3.5	
100-315J	O	30	34	51	5.44	11	2.0	1450
		50	32	63	6.92		2.0	
		60	30	64	7.67		2.5	
	A	28	29.3	51	4.43	11	2.0	
		46.7	27.9	62.8	5.64		2.0	
		56	26.1	63.3	6.30		2.25	
	B	26.3	26.1	51	3.66	7.5	2.0	
		43.8	24.6	62.7	4.67		2.0	
		52.6	23.0	62.2	5.30		2.10	
	C	24.3	22.3	50	2.89	5.5	2.0	
		40.5	21.0	61.5	3.86		2.0	
		48.36	19.7	61.2	4.25		2.0	
125-160	Z	105	42.8	72	16.9	30	5.6	2900
		174	38	80	22.6		5.6	
		209	33.3	77	24.6		5.6	
	O	96	36	72	13.1	22	5.6	
		160	32	80	17.5		5.6	
		192	28	77	19.0		5.6	
	A	89.8	31.5	70	11.0	18.5	5.6	
		150	28	85	14.7		5.6	
		180	24.5	75	16.0		5.6	
	B	8.1	27	68	8.99	15	5.6	
		139	24	76	11.9		5.6	
		166	21	73	13.0		5.6	
125-160J	Z	52.3	10.7	69	2.21	4	2.5	1450
		87.2	9.5	77	2.93		2.5	
		105	8.31	74	3.20		2.5	
	O	48	9	69	1.71	3	2.5	
		80	8	77	2.26		2.5	
		96	7	74	2.47		2.5	
型号	叶轮型式	流量 m ³ /h	扬程 m	效率%	功率 Kw		必需汽蚀余量 m	转速 r/min
					轴功率	电机功率		
125-160J	A	44.9	7.9	67	1.44	2.2	2.5	1450
		74.8	7	75	1.90		2.5	
		89.8	6.1	72	2.08		2.5	
	B	41.6	6.8	65	1.18	2.2	2.5	
		69.3	6	73	1.55		2.5	
83.1	5.3	70	1.70	2.5				
125-200 (I)	Z	105	66	65	28.6	45	5.2	2900
		175	60	80	35.8		5.2	
		210	55.2	78	40.5		5.2	

	0	96 160 192	55 5 46	65 80 78	21.8 27.2 30.8	37	5.2	
	A	90.1 150 180	48.4 44 40.5	65 79 77	18.3 22.8 25.8	30	5.2	
	B	83.6 139 167	41.8 38 35.0	64 78 76	14.9 18.5 21.0	22	5.2	
125-200J (I)	Z	52.6 87.6 105	16.5 15 13.8	63 77 75	3.75 4.65 5.27	5.5	2.5	1450
	0	48 80 96	13.6 12.5 11.5	63 77 75	2.85 3.54 4.00	4	2.5	
	A	45 75.1 90.1	12.1 11 10.1	62 76 74	2.39 2.96 3.35	4	2.5	
	B	41.9 69.7 83.7	10.5 9.5 8.7	61 75 73	1.95 2.41 2.73	3	2.5	
125-250 (I)	Z	103 172 206	100 92 84	65 77 74	43.2 55.8 63.9	75	4.8	2900
	0	96 160 192	87 80 73	65 77 74	35.0 45.3 51.6	55	4.8	
	A	89.8 150 180	76.1 70 63.9	64 76 73	29.1 37.5 42.8	45	4.8	
	B	83.1 139 166	65.3 60 54.8	53 75 72	23.5 30.2 34.4	37	4.5	
125-250J (I)	Z	51.5 85.8 103	25 23 21.3	62 74 71	5.66 7.26 8.48	11	2.2	1450
	0	48 80 69	21.8 20 18.3	62 74 71	4.59 5.89 6.72	7.5	2.2	
	A	44.9 748 89.8	19.0 17.5 16	61 73 70	3.81 4.89 5.58	5.5	2.2	

	B	41.6 69.3 83.1	16.3 15 13.7	60 72 69	3.08 3.93 4.49	5.5	2.2	
型号	叶轮型式	流量 m ³ /h	扬程 m	效率%	功率 Kw		必需汽蚀余量 m	转速 r/min
					轴功率	电机功率		
125-315 (I)	Z	100	145	58	68	110	4.5	2900
		167	136	73	84.7			
		200	129	73	96.7			
	O	96	133	58	60.0	90	4.5	
		160	125	73	74.6			
		192	119	73	85.2			
	A	91.7	121	57	53.1	75	4.5	
		153	114	72	65.9			
		183	109	72	75.3			
	B	87.1	110	56	46.4	75	4.5	
		145	103	71	57.4			
		174	98.1	71	65.6			
	C	82.4	97.4	53	39.9	75	4.5	
		137	92	58	49.1			
		165	87.4	68	56.1			
125-315J (I)	Z	49.5	35.6	55	8.72	15	2.1	1450
		82.5	34	70	10.9			
		99	31.9	70	12.3			
	O	48	33.5	55	7.96	15	2.1	
		80	32	74	9.96			
		96	30	71	11.2			
	A	45.3	29.8	54	6.68	11	2.1	
		75.5	28.5	69	8.49			
		90.3	26.7	69	9.55			
	B	43.1	27	53	5.97	11	2.1	
		71.8	25.8	68	7.40			
		86.1	24.1	68	8.33			
	C	40.7	24.1	52	5.13	7.5	2.1	
		67.8	23	67	6.37			
		81.4	21.6	67	7.13			
125-200 (II)	O	120	57.5	67	28.0	45	4.5	2900
		200	50	81	33.6		4.5	
		240	44.5	80	36.4		5.0	
	A	111	49.3	64.5	23.1	37	4.5	
		185	42.9	78	27.7		4.5	
		222	38.2	77	30.0		4.7	
	B	103	42.6	62.5	19.2	30	4.5	

	C	172	37.1	75	23.2	30	4.5	
		207	33.0	74	25.1		4.5	
		94.4	35.6	60	15.3		4.5	
		157	31.0	71	18.7		4.5	
		189	27.9	70	20.3		4.5	
125-200J (II)	O	60	14.5	62	3.83	7.5	2.5	1450
		100	12.5	76	4.48		2.5	
		120	11	75	4.79		3.0	
	A	55.6	12.4	61	3.08	5.5	2.5	
		92.6	10.7	73.5	3.68		2.5	
		111	9.4	73	3.91		2.75	
	B	51.7	10.8	58	2.61	5.5	2.5	
		86.1	9.3	70	3.11		2.5	
	C	103	8.2	69	3.33	4	2.55	
		47.2	9.0	55	2.10		2.5	
		78.7	7.7	66	2.51		2.5	
			94.4	6.8	66	2.66		

型号	叶轮型式	流量 m ³ /h	扬程 m	效率 %	功率 KW		必需汽蚀余量 m	转速 r/min
					轴功率	电机功率		
125-250 (II)	O	120	87	66	43	75	3.8	2900
		200	80	78	55.9		4.2	
		240	72	75	62.8		5.0	
	A	112	75.5	66	35.0	75	3.8	
		187	69.7	78.2	45.3		4.0	
		224	62.7	73.5	52.1		4.6	
	B	104	65.6	66	28.4	55	3.8	
		174	60.6	77	36.9		4.0	
	C	209	54.6	73	42.5	45	4.4	
		96.9	56.8	66	22.7		3.8	
		162	52.5	77.8	29.5		3.9	
			194	47	73	34.0		
125-250J (II)	O	60	21.5	63	5.59	11	2.5	1450
		100	20	76	7.17		2.5	
		120	18.5	77	7.84		3.0	
	A	56	18.7	63	4.53	11	2.5	
		93.3	17.4	76	5.83		2.5	
		112	16.1	77	6.38		2.7	
	B	52.2	16.3	63	3.68	7.5	2.5	
		87.1	15.2	75.5	4.76		2.5	
	C	104	14	76.8	5.19	5.5	2.53	
		48.5	14	53	2.94		2.5	

		80.8 96.6	13.1 12.1	75.2 76.5	3.82 4.17		2.5 2.5	
125-315 (II)	O	120	133	60	72.1	110	5.0	2900
		200	125	75	90.8		4.5	
		240	120	77	102		5.0	
	A	112	116	59	60.4	110	4.9	
		187	110	73.5	76.4		4.7	
		225	105	75	85.9		4.4	
	B	104	100	58	49.3	90	4.3	
		174	94.8	70.8	63.5		4.5	
		209	91.0	73.1	70.8		4.0	
C	96.5	85.7	57	39.5	75	4.0		
	161	80.9	68.4	51.8		4.2		
	193	77.7	71.3	57.3		4.4		
125-315J (II)	O	60	33.5	58	9.4	15	2.5	1450
		100	32	73	11.9		2.5	
		120	30.5	74	13.5		3.0	
	A	56.2	29.4	56	8.04	15	2.5	
		93.7	28.1	71.5	10.0		2.5	
		112	26.8	72.5	11.3		2.8	
	B	52.2	25.4	54	6.69	15	2.5	
		87.1	24.3	69.5	8.58		2.5	
		104	23.1	70.5	9.33		2.6	
C	48.3	21.7	53	5.38	11	2.5		
	80.4	20.7	67	6.77		2.5		
	96.5	19.7	68	7.63		2.5		
125-400J (I)	O	52.6	63.6	51	17.5	30	2.0	1450
		87.6	60	63	22.7			
		105	55.2	63	25			
	A	48	53	51	13.6	22	2.0	
		80	50469	63	17.3			
		96		63	19.1			
型号	叶轮型式	流量 m ³ /h	扬程 m	效率%	功率 KW		必需汽蚀余量 m	转速 r/min
					轴功率	电机功率		
125-400J(I)	B	45.6	46.6	50	11.4	18.5	2.0	1450
		75.1	44	62	14.5			
		90.1	40.5	62	16.0			
	C	41.9	40.3	49	9.4	15	2.0	
		69.7	38	61	11.8			
		83.7	35	61	13			
125-400J(II)	O	60	52	53	16.1	30	2.5	1450
		100	50	65	21		2.5	

		209	35	72.4	27.5		3.0	
	C	96.5	34.4	62	14.5	30	2.0	
		161	32.3	72.8	19.4		2.4	
		193	29.7	71.4	21.9		2.7	
型号	叶轮型式	流量 m ³ /h	扬程 m	效率%	功率 KW		必需汽蚀余量 m	转速 r/min
					轴功率	电机功率		
200-250	O	240	25	69	23.7	37	3.0	1450
		400	22	82.5	29.1		3.5	
		460	20	82	30.6		4.0	
	A	223	21.5	67	19.5	30	3.0	
		371	18.9	80	23.9		3.4	
		427	17.2	79.5	25.2		3.7	
	B	207	18.6	65.4	16.0	30	3.0	
		345	16.4	77.5	19.8		3.3	
		397	14.9	77	20.9		3.5	
	C	190	15.7	64.4	12.7	22	3.0	
		317	13.8	74	16.2		3.2	
		365	12.6	73.5	17.0		3.4	
200-315	O	240	37	70	34.6	55	3.0	1450
		400	32	82	42.5		3.5	
		460	28.5	80	44.5		4.0	
	A	219	30.9	68	27.2	45	3.0	
		369	26.7	76.2	35.0		3.4	
		420	23.8	75	36.4		3.6	
	B	198	25.2	61.5	22.1	37	3.0	
		330	21.8	69.3	28.3		3.2	
		380	19.4	69	29.1		3.4	
	C	182	21.2	58	18.1	30	3.0	
		303	18.3	64	23.6		3.1	
		348	16.3	62	24.9		3.3	
200-400	O	240	55	74	48.6	90	3.0	1450
		400	50	81	67.2		3.8	
		460	45	76	74.2		4.5	
	A	224	47.7	73	39.8	75	3.0	
		373	43.4	79.8	55.2		3.6	
		429	39.1	73.5	62.0		4.1	
	B	209	41.7	72	33.0	75	3.0	
		348	37.9	78.6	45.8		3.4	
		401	34.1	72	51.7		3.8	
	C	194	36.1	71	26.9	55	3.0	
		324	32.8	77	37.6		3.25	
		373	29.5	70.5	42.5		3.6	

250-315	Z	380	41	71	59.7	90	4.8	1480	
		630	38	84.5	77.1		5.5		
		760	35	84	86.2		7		
	O	380	31.6	71	51.7	75	4.8		
630		28.5	84.5	65	5.5				
250-400	A	720	25.8	84	71.4	75	7	1480	
		360	31.6	69.5	44.6		55		4.7
		590	28.5	55.1	55.1				5.4
	B	720	25.8	61.3	61.3	75	6.9		
340		27.7	68.5	37.4	55		4.6		
250-400	Z	560	25	82		46.5	132	5.3	1480
		670	22.6	81.5	50.6	6.8			
		380	60	74	83.9	132		4.9	
	630	54.5	84.5	110.4	5.5				
O	760	50.8	85	123.6	132	6.9			
	380	56	74	78.3		132	4.9		
	630	50	84.5	101.5			5.5		
250-400	A	760	44.8	83.5	111	132	6.9	1480	
		380	60	74	83.9		132		4.9
		630	54.5	84.5	110.4				5.5
250-400	B	760	50.8	85	123.6	132	6.9	1480	
		380	56	74	78.3		132		4.9
		630	50	84.5	101.5				5.5
250-400	C	760	44.8	83.5	111	132	6.9	1480	
		380	56	74	78.3		132		4.9
		630	50	84.5	101.5				5.5
250-400	Z	760	44.8	83.5	111	132	6.9	1480	
		380	56	74	78.3		132		4.9
		630	50	84.5	101.5				5.5
250-400	O	760	44.8	83.5	111	132	6.9	1480	
		380	56	74	78.3		132		4.9
		630	50	84.5	101.5				5.5
250-400	A	760	44.8	83.5	111	132	6.9	1480	
		380	56	74	78.3		132		4.9
		630	50	84.5	101.5				5.5
250-400	B	760	44.8	83.5	111	132	6.9	1480	
		380	56	74	78.3		132		4.9
		630	50	84.5	101.5				5.5
250-400	C	760	44.8	83.5	111	132	6.9	1480	
		380	56	74	78.3		132		4.9
		630	50	84.5	101.5				5.5
300-315	Z	600	43.3	72	98.2	132	5.3	1480	
		1000	37.5	86	119		110		6.6
		1200	34	86	129				8.5
300-315	O	600	38	72	86.2	110	5.3	1480	
		1000	32	86	101.3		110		6.5
		1200	28	85	107.6				8.5
300-315	A	570	33.8	70.5	74.4	110	5.2	1480	
		940	28.5	84	86.8		110		6.4
		1130	24.8	83.5	91.4				8.4
300-315	B	530	29.7	69.5	61.7	90	4.9	1480	
		880	25	83	72.2		90		6.1
		1060	21.9	82.5	76.6				8.1
300-400	Z	600	75	73	167.8	250	5.5	1480	

型号	叶轮型式	流量 m ³ /h	扬程 m	效率%	功率 KW		必需汽蚀余量 m	转速 r/min
					轴功率	电机功率		

350-315		100	65	86	206		6.2	1480
		120	56	84	221.7		7.7	
	0	600	58	73	129.8	185	5.5	
		1000	50	86	158.3		6.2	
		1200	43	82.5	170.3		7.7	
	A	570	52	71	113.6	170	5.4	
		950	45	84	138.5		6.1	
		1140	39	82	147.6		7.6	
	B	540	46.4	70.5	96.7	130	5.3	
		890	40	83.5	116		6	
		1070	34.4	81	123.7		7.5	
	0	960	38.4	77	130	185	6.1	
		1600	32	85	164		7	
		1920	26.5	82	169		8.9	
	A	910	34.2	75	113	160	5.9	
	1510	28.5	83	141.2	6.8			
	1810	23.6	80	145.4	8.7			
B	850	30	74	93.8	132	5.6		
	1410	25	81.5	118		6.5		
	1700	20.5	79	120		8.4		
350-400	0	960	56.5	77	191.8	280	6.3	1480
		1600	50	87	250.3		7.2	
		1920	44	84	273.8		9.1	
	A	910	50.8	75.5	166.7	250	5.9	
		1520	45	85.5	217.8		6.8	
		1820	39.5	82.5	237.2		8.7	
	B	860	45.2	75	141.1	220	5.6	
		1430	40	84.5	184.3		6.5	
		1720	35.2	81.5	202.2		8.4	
	C	800	39.5	74	116.3	185	5.5	
	1340	35	83.5	153	6.4			
	1610	30.8	80.5	167.7	8.3			